

# General Purpose Transistors


## NPN Silicon

- We declare that the material of product compliance with RoHS requirements.
- S- Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable.

### ORDERING INFORMATION


Device	Marking	Shipping
L2SC2412KQLT1G S-L2SC2412KQLT1G	BQ	3000 Tape & Reel
L2SC2412KQLT3G S-L2SC2412KQLT3G	BQ	10000 Tape & Reel
L2SC2412KRLT1G S-L2SC2412KRLT1G	BR	3000 Tape & Reel
L2SC2412KRLT3G S-L2SC2412KRLT3G	BR	10000 Tape & Reel
L2SC2412KSLT1G S-L2SC2412KSLT1G	G1F	3000 Tape & Reel
L2SC2412KSLT3G S-L2SC2412KSLT3G	G1F	10000 Tape & Reel

L2SC2412KQLT1G  
Series  
L2SC2412KQLT1G  
Series



### MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector–Emitter Voltage	$V_{CEO}$	50	V
Collector–Base Voltage	$V_{CBO}$	60	V
Emitter–Base Voltage	$V_{EBO}$	7.0	V
Collector Current — Continuous	$I_C$	150	mAdc
Collector power dissipation	$P_C$	0.2	W
Junction temperature	$T_j$	150	°C
Storage temperature	$T_{stg}$	-55 ~ +150	°C



### DEVICE MARKING

L2SC2412KQLT1G =BQ L2SC2412KRLT1G =BR L2SC2412KSLT1G =G1F

### ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ unless otherwise noted.)

Characteristic	Symbol	Min	Typ	Max	Unit
Collector–Emitter Breakdown Voltage ( $I_C = 1\text{ mA}$ )	$V_{(BR)CEO}$	50	—	—	V
Emitter–Base Breakdown Voltage ( $I_E = 50\ \mu\text{A}$ )	$V_{(BR)EBO}$	7	—	—	V
Collector–Base Breakdown Voltage ( $I_C = 50\ \mu\text{A}$ )	$V_{(BR)CBO}$	60	—	—	V
Collector Cutoff Current ( $V_{CB} = 60\text{ V}$ )	$I_{CBO}$	—	—	0.1	$\mu\text{A}$
Emitter cutoff current ( $V_{EB} = 7\text{ V}$ )	$I_{EBO}$	—	—	0.1	$\mu\text{A}$
Collector-emitter saturation voltage ( $I_C / I_B = 50\text{ mA} / 5\text{ mA}$ )	$V_{CE(sat)}$	—	—	0.4	V
DC current transfer ratio ( $V_{CE} = 6\text{ V}, I_C = 1\text{ mA}$ )	$h_{FE}$	120	—	560	—
Transition frequency ( $V_{CE} = 12\text{ V}, I_E = -2\text{ mA}, f = 30\text{ MHz}$ )	$f_T$	—	180	—	MHz
Output capacitance ( $V_{CB} = 12\text{ V}, I_E = 0\text{ A}, f = 1\text{ MHz}$ )	$C_{ob}$	—	2.0	3.5	pF

### $h_{FE}$ values are classified as follows:

*	Q	R	S
$h_{FE}$	120~270	180~390	270~560

L2SC2412KQLT1G Series

S-L2SC2412KQLT1G Series

Fig.1 Grounded emitter propagation characteristics




Fig.2 Grounded emitter output characteristics(I)




Fig.3 Grounded emitter output characteristics(II)




Fig.4 DC current gain vs. collector current (I)




Fig.5 DC current gain vs. collector current (II)





Fig.6 Collector-emitter saturation voltage vs. collector current



L2SC2412KQLT1G Series

S-L2SC2412KQLT1G Series

Fig.7 Collector-emitter saturation voltage vs. collector current (I)




Fig.8 Collector-emitter saturation voltage vs. collector current (II)




Fig.9 Gain bandwidth product vs. emitter current




Fig.10 Collector output capacitance vs. collector-base voltage  
Emitter input capacitance vs. emitter-base voltage






Fig.11 Base-collector time constant vs. emitter current



SOT-23

NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M,1982
2. CONTROLLING DIMENSION: INCH.



DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.1102	0.1197	2.80	3.04
B	0.0472	0.0551	1.20	1.40
C	0.0350	0.0440	0.89	1.11
D	0.0150	0.0200	0.37	0.50
G	0.0701	0.0807	1.78	2.04
H	0.0005	0.0040	0.013	0.100
J	0.0034	0.0070	0.085	0.177
K	0.0140	0.0285	0.35	0.69
L	0.0350	0.0401	0.89	1.02
S	0.0830	0.1039	2.10	2.64
V	0.0177	0.0236	0.45	0.60

